

1.1

1.1 The force, F , of the wind blowing against a building is given by $F = C_D \rho V^2 A / 2$, where V is the wind speed, ρ the density of the air, A the cross-sectional area of the building, and C_D is a constant termed the drag coefficient. Determine the dimensions of the drag coefficient.

$$F = C_D \rho V^2 A / 2$$

or

$$C_D = 2F / \rho V^2 A, \text{ where } F \doteq MLT^{-2}$$

$$\rho \doteq ML^{-3}$$

$$V \doteq LT^{-1}$$

$$A \doteq L^2$$

Thus,

$$C_D \doteq (MLT^{-2}) / [(ML^{-3})(LT^{-1})^2(L^2)] = M^0 L^0 T^0$$

Hence, C_D is dimensionless.

1.2 Determine the dimensions, in both the FLT system and the MLT system, for (a) the product of mass times velocity, (b) the product of force times volume, and (c) kinetic energy divided by area.

$$(a) \text{ mass} \times \text{velocity} \doteq (M)(LT^{-1}) \doteq \underline{\underline{MLT^{-1}}}$$

$$\text{Since } F \doteq MLT^{-2}$$

$$\text{mass} \times \text{velocity} \doteq (FL^{-1}T^2)(LT^{-1}) \doteq \underline{\underline{FT}}$$

$$(b) \text{ force} \times \text{volume} \doteq \underline{\underline{FL^3}}$$

$$\doteq (MLT^{-2})(L^3) \doteq \underline{\underline{ML^4T^{-2}}}$$

$$(c) \frac{\text{kinetic energy}}{\text{area}} \doteq \frac{FL}{L^2} \doteq \underline{\underline{FL^{-1}}}$$

$$\doteq \frac{(MLT^{-2})L}{L^2} \doteq \underline{\underline{MT^{-2}}}$$

1.3

1.3 Verify the dimensions, in both the *FLT* and *MLT* systems, of the following quantities which appear in Table 1.1: (a) volume, (b) acceleration, (c) mass, (d) moment of inertia (area), and (e) work.

$$(a) \text{ volume} \doteq \underline{\underline{L^3}}$$

$$(b) \text{ acceleration} = \text{time rate of change of velocity} \\ \doteq \frac{LT^{-1}}{T} \doteq \underline{\underline{LT^{-2}}}$$

$$(c) \text{ mass} \doteq \underline{\underline{M}} \\ \text{or with } F \doteq MLT^{-2} \\ \text{mass} \doteq \underline{\underline{FL^{-1}T^2}}$$

$$(d) \text{ moment of inertia (area)} = \text{second moment of area} \\ \doteq (L^2)(L^2) \doteq \underline{\underline{L^4}}$$

$$(e) \text{ work} = \text{force} \times \text{distance} \\ \doteq \underline{\underline{FL}} \\ \text{or with } F \doteq MLT^{-2} \\ \text{work} \doteq \underline{\underline{ML^2T^{-2}}}$$

1.4 Determine the dimensions, in both the *FLT* system and the *MLT* system, for (a) the product of force times acceleration, (b) the product of force times velocity divided by area, and (c) momentum divided by volume.

$$(a) \text{ force} \times \text{acceleration} \doteq (F)(LT^{-2}) \doteq \underline{\underline{FLT^{-2}}}$$

$$\text{Since } F \doteq MLT^{-2},$$

$$\text{force} \times \text{acceleration} \doteq (MLT^{-2})(LT^{-2}) \doteq \underline{\underline{ML^2T^{-4}}}$$

$$(b) \frac{\text{force} \times \text{velocity}}{\text{area}} \doteq \frac{(F)(LT^{-1})}{L^2} \doteq \underline{\underline{FL^{-1}T^{-1}}}$$

$$\doteq \frac{(MLT^{-2})(LT^{-1})}{L^2} \doteq \underline{\underline{MT^{-3}}}$$

$$(c) \frac{\text{momentum}}{\text{volume}} = \frac{\text{mass} \times \text{velocity}}{\text{volume}}$$

$$\doteq \frac{(FT^2L^{-1})(LT^{-1})}{L^3} \doteq \underline{\underline{FL^{-3}T}}$$

$$\doteq \frac{(M)(LT^{-1})}{L^3} \doteq \underline{\underline{ML^{-2}T^{-1}}}$$

1.5 Verify the dimensions, in both the FLT and MLT systems, of the following quantities which appear in Table 1.1: (a) angular velocity, (b) energy, (c) moment of inertia (area), (d) power, and (e) pressure.

$$(a) \text{ angular velocity} = \frac{\text{angular displacement}}{\text{time}} \doteq \underline{\underline{T^{-1}}}$$

(b) energy \sim capacity of body to do work

Since work = force \times distance,

$$\text{energy} \doteq \underline{\underline{FL}}$$

or with $F \doteq MLT^{-2}$

$$\text{energy} \doteq (MLT^{-2})(L) \doteq \underline{\underline{ML^2T^{-2}}}$$

(c) moment of inertia (area) = second moment of area

$$\doteq (L^2)(L^2) \doteq \underline{\underline{L^4}}$$

(d) power = rate of doing work $\doteq \frac{FL}{T} \doteq \underline{\underline{FLT^{-1}}}$

$$\doteq (MLT^{-2})(L)(T^{-1}) \doteq \underline{\underline{ML^2T^{-3}}}$$

(e) pressure = $\frac{\text{force}}{\text{area}} \doteq \frac{F}{L^2} \doteq \underline{\underline{FL^{-2}}}$

$$\doteq (MLT^{-2})(L^{-2}) \doteq \underline{\underline{ML^{-1}T^{-2}}}$$

1.6 Verify the dimensions, in both the *FLT* system and the *MLT* system, of the following quantities which appear in Table 1.1: (a) frequency, (b) stress, (c) strain, (d) torque, and (e) work.

$$(a) \text{ frequency} = \frac{\text{cycles}}{\text{time}} \doteq \underline{\underline{T^{-1}}}$$

$$(b) \text{ stress} = \frac{\text{force}}{\text{area}} \doteq \frac{F}{L^2} \doteq \underline{\underline{FL^{-2}}}$$

$$\text{Since } F \doteq MLT^{-2},$$

$$\text{stress} \doteq \frac{MLT^{-2}}{L^2} \doteq \underline{\underline{ML^{-1}T^{-2}}}$$

$$(c) \text{ strain} = \frac{\text{change in length}}{\text{length}} \doteq \frac{L}{L} \doteq \underline{\underline{L^0}} \text{ (dimensionless)}$$

$$(d) \text{ torque} = \text{force} \times \text{distance} \doteq \underline{\underline{FL}}$$

$$\doteq (MLT^{-2})(L) \doteq \underline{\underline{ML^2T^{-2}}}$$

$$(e) \text{ work} = \text{force} \times \text{distance} \doteq \underline{\underline{FL}}$$

$$\doteq (MLT^{-2})(L) \doteq \underline{\underline{ML^2T^{-2}}}$$

1.7

1.7 If u is a velocity, x a length, and t a time, what are the dimensions (in the MLT system) of (a) $\partial u/\partial t$, (b) $\partial^2 u/\partial x \partial t$, and (c) $\int (\partial u/\partial t) dx$?

$$(a) \frac{\partial u}{\partial t} \doteq \frac{LT^{-1}}{T} \doteq \underline{\underline{LT^{-2}}}$$

$$(b) \frac{\partial^2 u}{\partial x \partial t} \doteq \frac{LT^{-1}}{(L)(T)} \doteq \underline{\underline{T^{-2}}}$$

$$(c) \int \frac{\partial u}{\partial t} dx \doteq \frac{(LT^{-1})}{T} (L) \doteq \underline{\underline{L^2 T^{-2}}}$$

1.8 Verify the dimensions, in both the FLT system and the MLT system, of the following quantities which appear in Table 1.1: (a) acceleration, (b) stress, (c) moment of a force, (d) volume, and (e) work.

$$(a) \text{ acceleration} = \frac{\text{velocity}}{\text{time}} \doteq \frac{L}{T^2} \doteq \underline{\underline{LT^{-2}}}$$

$$(b) \text{ stress} = \frac{\text{force}}{\text{area}} \doteq \frac{F}{L^2} \doteq \underline{\underline{FL^{-2}}}$$

$$\text{Since } F \doteq MLT^{-2},$$

$$\text{stress} \doteq \frac{MLT^{-2}}{L^2} = \underline{\underline{ML^{-1}T^{-2}}}$$

$$(c) \text{ moment of a force} = \text{force} \times \text{distance} \doteq \underline{\underline{FL}} \\ \doteq (MLT^{-2})L \doteq \underline{\underline{ML^2T^{-2}}}$$

$$(d) \text{ volume} = (\text{length})^3 \doteq \underline{\underline{L^3}}$$

$$(e) \text{ work} = \text{force} \times \text{distance} \doteq \underline{\underline{FL}} \\ \doteq (MLT^{-2})L \doteq \underline{\underline{ML^2T^{-2}}}$$

1.9

1.9 If p is a pressure, V a velocity, and ρ a fluid density, what are the dimensions (in the MLT system) of (a) p/ρ , (b) $pV\rho$, and (c) $p/\rho V^2$?

$$(a) \frac{p}{\rho} \doteq \frac{ML^{-1}T^{-2}}{ML^{-3}} \doteq \underline{\underline{L^2 T^{-2}}}$$

$$(b) pV\rho \doteq (ML^{-1}T^{-2})(LT^{-1})(ML^{-3}) \doteq \underline{\underline{M^2 L^{-3} T^{-3}}}$$

$$(c) \frac{p}{\rho V^2} \doteq \frac{ML^{-1}T^{-2}}{(ML^{-3})(LT^{-1})^2} \doteq M^0 L^0 T^0 \text{ (dimensionless)}$$

1.10

1.10 If P is a force and x a length, what are the dimensions (in the FLT system) of (a) dP/dx , (b) d^3P/dx^3 , and (c) $\int P dx$?

$$(a) \frac{dP}{dx} \doteq \frac{F}{L} \doteq \underline{\underline{FL^{-2}}}$$

$$(b) \frac{d^3P}{dx^3} \doteq \frac{F}{L^3} \doteq \underline{\underline{FL^{-3}}}$$

$$(c) \int P dx \doteq \underline{\underline{FL}}$$

1.11

1.11 If V is a velocity, ℓ a length, and ν a fluid property (the kinematic viscosity) having dimensions of L^2T^{-1} , which of the following combinations are dimensionless: (a) $V\ell\nu$, (b) $V\ell/\nu$, (c) $V^2\nu$, (d) $V/\ell\nu$?

$$(a) V\ell\nu \doteq (LT^{-1})(L)(L^2T^{-1}) \doteq L^4T^{-2} \text{ (not dimensionless)}$$

$$(b) \frac{V\ell}{\nu} \doteq \frac{(LT^{-1})(L)}{(L^2T^{-1})} \doteq L^0T^0 \text{ (dimensionless)}$$

$$(c) V^2\nu \doteq (LT^{-1})^2(L^2T^{-1}) \doteq L^4T^{-3} \text{ (not dimensionless)}$$

$$(d) \frac{V}{\ell\nu} \doteq \frac{(LT^{-1})}{(L)(L^2T^{-1})} \doteq L^{-2} \text{ (not dimensionless)}$$

1.12

1.12 If V is a velocity, determine the dimensions of Z , α , and G , which appear in the dimensionally homogeneous equation

$$V = Z(\alpha - 1) + G$$

$$V = Z(\alpha - 1) + G$$

$$[LT^{-1}] = [Z][\alpha - 1] + [G]$$

Since each term in the equation must have the same dimensions, it follows that

$$Z = \underline{LT^{-1}}$$

$$\alpha = \underline{F^0 L^0 T^0} \text{ (dimensionless since combined with a number)}$$

$$G = \underline{LT^{-1}}$$

1.13

1.13 The volume rate of flow, Q , through a pipe containing a slowly moving liquid is given by the equation

$$Q = \frac{\pi R^4 \Delta p}{8\mu \ell}$$

where R is the pipe radius, Δp the pressure drop along the pipe, μ a fluid property called viscosity ($FL^{-2}T$), and ℓ the length of pipe. What are the dimensions of the constant $\pi/8$? Would you classify this equation as a general homogeneous equation? Explain.

$$[L^3 T^{-1}] \doteq \left[\frac{\pi}{8} \right] \frac{[L^4][FL^{-2}]}{[FL^{-2}T][L]}$$

$$[L^3 T^{-1}] \doteq \left[\frac{\pi}{8} \right] [L^3 T^{-1}]$$

The constant $\pi/8$ is dimensionless, and the equation is a general homogeneous equation that is valid in any consistent unit system. Yes.

1.14

1.14 According to information found in an old hydraulics book, the energy loss per unit weight of fluid flowing through a nozzle connected to a hose can be estimated by the formula

$$h = (0.04 \text{ to } 0.09)(D/d)^4 V^2 / 2g$$

where h is the energy loss per unit weight, D the hose diameter, d the nozzle tip diameter, V the fluid velocity in the hose, and g the acceleration of gravity. Do you think this equation is valid in any system of units? Explain.

$$h = (0.04 \text{ to } 0.09) \left(\frac{D}{d}\right)^4 \frac{V^2}{2g}$$

$$\left[\frac{FL}{F}\right] \doteq [0.04 \text{ to } 0.09] \left[\frac{L^4}{L^4}\right] \left[\frac{1}{2}\right] \left[\frac{L^2}{T^2}\right] \left[\frac{T^2}{L}\right]$$

$$[L] \doteq [0.04 \text{ to } 0.09] [L]$$

Since each term in the equation must have the same dimensions, the constant term (0.04 to 0.09) must be dimensionless. Thus, the equation is a general homogeneous equation that is valid in any system of units. Yes.

1.15

1.15 The pressure difference, Δp , across a partial blockage in an artery (called a *stenosis*) is approximated by the equation

$$\Delta p = K_v \frac{\mu V}{D} + K_u \left(\frac{A_0}{A_1} - 1\right)^2 \rho V^2$$

where V is the blood velocity, μ the blood vis-

cosity ($FL^{-2}T$), ρ the blood density (ML^{-3}), D the artery diameter, A_0 the area of the unobstructed artery, and A_1 the area of the stenosis. Determine the dimensions of the constants K_v and K_u . Would this equation be valid in any system of units?

$$\Delta p = K_v \frac{\mu V}{D} + K_u \left[\frac{A_0}{A_1} - 1\right]^2 \rho V^2$$

$$[FL^{-2}] \doteq [K_v] \left[\left(\frac{FT}{L^2}\right)\left(\frac{L}{T}\right)\left(\frac{1}{L}\right)\right] + [K_u] \left[\left(\frac{L^2}{L^2}\right) - 1\right]^2 \left[\frac{FT^2}{L^4}\right] \left[\frac{L}{T}\right]^2$$

$$[FL^{-2}] \doteq [K_v] [FL^{-2}] + [K_u] [FL^{-2}]$$

Since each term must have the same dimensions, K_v and K_u are dimensionless. Thus, the equation is a general homogeneous equation that would be valid in any consistent system of units. Yes.

1.16

1.16 Assume that the speed of sound, c , in a fluid depends on an elastic modulus, E_v , with dimensions FL^{-2} , and the fluid density, ρ , in the form $c = (E_v)^a (\rho)^b$. If this is to be a dimensionally homogeneous equation, what are the values for a and b ? Is your result consistent with the standard formula for the speed of sound? (See Eq. 1.19.)

$$c = (E_v)^a (\rho)^b$$

$$\text{Since } c \doteq LT^{-1} \quad E_v \doteq FL^{-2} \quad \rho = FL^{-3}T^{-2}$$

$$\left[\frac{L}{T} \right] = \left[\frac{F^a}{L^{-2a}} \right] \left[\frac{F^b T^{2b}}{L^{-3b}} \right] \quad (1)$$

For a dimensionally homogeneous equation each term in the equation must have the same dimensions. Thus, the right hand side of Eq. (1) must have the dimensions of LT^{-1} . Therefore,

$$a + b = 0 \quad (\text{to eliminate } F)$$

$$2b = -1 \quad (\text{to satisfy condition on } T)$$

$$2a + 4b = -1 \quad (\text{to satisfy condition on } L)$$

$$\text{It follows that } a = \frac{1}{2} \quad \text{and} \quad b = -\frac{1}{2}$$

So that

$$c = \sqrt{\frac{E_v}{\rho}}$$

This result is consistent with the standard formula for the speed of sound. Yes.

1.17

1.17 A formula to estimate the volume rate of flow, Q , flowing over a dam of length, B , is given by the equation

$$Q = 3.09BH^{3/2}$$

where H is the depth of the water above the top

of the dam (called the head). This formula gives Q in ft^3/s when B and H are in feet. Is the constant, 3.09, dimensionless? Would this equation be valid if units other than feet and seconds were used?

$$Q = 3.09 B H^{3/2}$$

$$[L^3 T^{-1}] \doteq [3.09][L][L]^{3/2}$$

$$[L^3 T^{-1}] \doteq [3.09][L]^{5/2}$$

Since each term in the equation must have the same dimensions the constant 3.09 must have dimensions of $L^{1/2} T^{-1}$ and is therefore not dimensionless. No.

Since the constant has dimensions its value will change with a change in units. No.

1.18 The force, P , that is exerted on a spherical particle moving slowly through a liquid is given by the equation

$$P = 3\pi\mu DV$$

where μ is a fluid property (viscosity) having dimensions of $FL^{-2}T$, D is the particle diameter, and V is the particle velocity. What are the dimensions of the constant, 3π ? Would you classify this equation as a general homogeneous equation?

$$P = 3\pi\mu DV$$

$$[F] \doteq [3\pi][FL^{-2}T][L][LT^{-1}]$$

$$[F] \doteq [3\pi][F]$$

$\therefore 3\pi$ is dimensionless, and the equation is a general homogeneous equation. Yes.

1.20

1.20 Make use of Table 1.3 to express the following quantities in SI units: (a) 10.2 in./min, (b) 4.81 slugs, (c) 3.02 lb, (d) 73.1 ft/s², (e) 0.0234 lb·s/ft².

$$(a) 10.2 \frac{\text{in.}}{\text{min}} = \left(10.2 \frac{\text{in.}}{\text{min}}\right) \left(2.540 \times 10^{-2} \frac{\text{m}}{\text{in.}}\right) \left(\frac{1 \text{ min}}{60 \text{ s}}\right)$$

$$= 4.32 \times 10^{-3} \frac{\text{m}}{\text{s}} = \underline{\underline{4.32 \frac{\text{mm}}{\text{s}}}}$$

$$(b) 4.81 \text{ slugs} = \left(4.81 \text{ slugs}\right) \left(1.459 \times 10 \frac{\text{kg}}{\text{slug}}\right) = \underline{\underline{70.2 \text{ kg}}}$$

$$(c) 3.02 \text{ lb} = \left(3.02 \text{ lb}\right) \left(4.448 \frac{\text{N}}{\text{lb}}\right) = \underline{\underline{13.4 \text{ N}}}$$

$$(d) 73.1 \frac{\text{ft}}{\text{s}^2} = \left(73.1 \frac{\text{ft}}{\text{s}^2}\right) \left(3.048 \times 10^{-1} \frac{\frac{\text{m}}{\text{s}^2}}{\frac{\text{ft}}{\text{s}^2}}\right) = \underline{\underline{22.3 \frac{\text{m}}{\text{s}^2}}}$$

$$(e) 0.0234 \frac{\text{lb}\cdot\text{s}}{\text{ft}^2} = \left(0.0234 \frac{\text{lb}\cdot\text{s}}{\text{ft}^2}\right) \left(4.788 \times 10 \frac{\frac{\text{N}\cdot\text{s}}{\text{m}^2}}{\frac{\text{lb}\cdot\text{s}}{\text{ft}^2}}\right)$$

$$= \underline{\underline{1.12 \frac{\text{N}\cdot\text{s}}{\text{m}^2}}}$$

1.21

1.21 Make use of Table 1.4 to express the following quantities in BG units: (a) 14.2 km, (b) 8.14 N/m³, (c) 1.61 kg/m³, (d) 0.0320 N·m/s, (e) 5.67 mm/hr.

$$(a) 14.2 \text{ km} = (14.2 \times 10^3 \text{ m}) \left(3.281 \frac{\text{ft}}{\text{m}} \right) = \underline{\underline{4.66 \times 10^4 \text{ ft}}}$$

$$(b) 8.14 \frac{\text{N}}{\text{m}^3} = \left(8.14 \frac{\text{N}}{\text{m}^3} \right) \left(6.366 \times 10^{-3} \frac{\frac{\text{lb}}{\text{ft}^3}}{\frac{\text{N}}{\text{m}^3}} \right) = \underline{\underline{5.18 \times 10^{-2} \frac{\text{lb}}{\text{ft}^3}}}$$

$$(c) 1.61 \frac{\text{kg}}{\text{m}^3} = \left(1.61 \frac{\text{kg}}{\text{m}^3} \right) \left(1.940 \times 10^{-3} \frac{\frac{\text{slugs}}{\text{ft}^3}}{\frac{\text{kg}}{\text{m}^3}} \right) = \underline{\underline{3.12 \times 10^{-3} \frac{\text{slugs}}{\text{ft}^3}}}$$

$$(d) 0.0320 \frac{\text{N}\cdot\text{m}}{\text{s}} = \left(0.0320 \frac{\text{N}\cdot\text{m}}{\text{s}} \right) \left(7.376 \times 10^{-1} \frac{\frac{\text{ft}\cdot\text{lb}}{\text{s}}}{\frac{\text{N}\cdot\text{m}}{\text{s}}} \right) \\ = \underline{\underline{2.36 \times 10^{-2} \frac{\text{ft}\cdot\text{lb}}{\text{s}}}}$$

$$(e) 5.67 \frac{\text{mm}}{\text{hr}} = \left(5.67 \times 10^{-3} \frac{\text{m}}{\text{hr}} \right) \left(3.281 \frac{\text{ft}}{\text{m}} \right) \left(\frac{1 \text{ hr}}{3600 \text{ s}} \right) \\ = \underline{\underline{5.17 \times 10^{-6} \frac{\text{ft}}{\text{s}}}}$$

1.22

1.22 Express the following quantities in SI units: (a) 160 acre,
 (b) 15 gallons (U.S.), (c) 240 miles, (d) 79.1 hp, (e) 60.3 °F.

$$(a) \quad 160 \text{ acre} = (160 \text{ acre}) \left(4.356 \times 10^4 \frac{\text{ft}^2}{\text{acre}} \right) \left(9.290 \times 10^{-2} \frac{\text{m}^2}{\text{ft}^2} \right) \\ = \underline{\underline{6.47 \times 10^5 \text{ m}^2}}$$

$$(b) \quad 15 \text{ gallons} = (15 \text{ gallons}) \left(3.785 \frac{\text{liters}}{\text{gallon}} \right) \left(10^{-3} \frac{\text{m}^3}{\text{liter}} \right) = \underline{\underline{56.8 \times 10^{-2} \text{ m}^3}}$$

$$(c) \quad 240 \text{ mi} = (240 \text{ mi}) \left(5280 \frac{\text{ft}}{\text{mi}} \right) \left(3.048 \times 10^{-1} \frac{\text{m}}{\text{ft}} \right) = \underline{\underline{3.86 \times 10^5 \text{ m}}}$$

$$(d) \quad 79.1 \text{ hp} = (79.1 \text{ hp}) \left(550 \frac{\text{ft} \cdot \text{lb}}{\text{s}} \right) \left(1.356 \frac{\text{J}}{\text{ft} \cdot \text{lb}} \right) = 5.90 \times 10^4 \frac{\text{J}}{\text{s}}$$

and $1 \frac{\text{J}}{\text{s}} = 1 \text{ W}$ so that

$$79.1 \text{ hp} = \underline{\underline{5.90 \times 10^4 \text{ W}}}$$

$$(e) \quad T_c = \frac{5}{9} (60.3^\circ \text{F} - 32) = 15.7^\circ \text{C}$$

$$= 15.7^\circ \text{C} + 273 = \underline{\underline{289 \text{ K}}}$$

1.23

1.23 For Table 1.3 verify the conversion relationships for: (a) area, (b) density, (c) velocity, and (d) specific weight. Use the basic conversion relationships: 1 ft = 0.3048 m; 1 lb = 4.4482 N; and 1 slug = 14.594 kg.

$$(a) \quad 1 \text{ ft}^2 = (1 \text{ ft}^2) \left[\frac{(0.3048)^2 \text{ m}^2}{\text{ft}^2} \right] = 0.09290 \text{ m}^2$$

Thus, multiply ft^2 by 9.290 E-2 to convert to m^2 .

$$(b) \quad 1 \frac{\text{slug}}{\text{ft}^3} = \left(1 \frac{\text{slug}}{\text{ft}^3} \right) \left(14.594 \frac{\text{kg}}{\text{slug}} \right) \left[\frac{1 \text{ ft}^3}{(0.3048)^3 \text{ m}^3} \right]$$

$$= 515.4 \frac{\text{kg}}{\text{m}^3}$$

Thus, multiply slugs/ft^3 by 5.154 E+2 to convert to kg/m^3 .

$$(c) \quad 1 \frac{\text{ft}}{\text{s}} = \left(1 \frac{\text{ft}}{\text{s}} \right) \left(0.3048 \frac{\text{m}}{\text{ft}} \right) = 0.3048 \frac{\text{m}}{\text{s}}$$

Thus, multiply ft/s by 3.048 E-1 to convert to m/s .

$$(d) \quad 1 \frac{\text{lb}}{\text{ft}^3} = \left(1 \frac{\text{lb}}{\text{ft}^3} \right) \left(4.4482 \frac{\text{N}}{\text{lb}} \right) \left[\frac{1 \text{ ft}^3}{(0.3048)^3 \text{ m}^3} \right]$$

$$= 157.1 \frac{\text{N}}{\text{m}^3}$$

Thus, multiply lb/ft^3 by 1.571 E+2 to convert to N/m^3 .

1.24

1.24 For Table 1.4 verify the conversion relationships for: (a) acceleration, (b) density, (c) pressure, and (d) volume flowrate. Use the basic conversion relationships: $1 \text{ m} = 3.2808 \text{ ft}$; $1 \text{ N} = 0.22481 \text{ lb}$; and $1 \text{ kg} = 0.068521 \text{ slug}$.

$$(a) \quad 1 \frac{\text{m}}{\text{s}^2} = \left(1 \frac{\text{m}}{\text{s}^2} \right) \left(3.2808 \frac{\text{ft}}{\text{m}} \right) = 3.281 \frac{\text{ft}}{\text{s}^2}$$

Thus, multiply m/s^2 by 3.281 to convert to ft/s^2 .

$$(b) \quad 1 \frac{\text{kg}}{\text{m}^3} = \left(1 \frac{\text{kg}}{\text{m}^3} \right) \left(0.068521 \frac{\text{slugs}}{\text{kg}} \right) \left[\frac{1 \text{ m}^3}{(3.2808)^3 \text{ ft}^3} \right]$$

$$= 1.940 \times 10^{-3} \frac{\text{slugs}}{\text{ft}^3}$$

Thus, multiply kg/m^3 by 1.940 E-3 to convert to slugs/ft^3 .

$$(c) \quad 1 \frac{\text{N}}{\text{m}^2} = \left(1 \frac{\text{N}}{\text{m}^2} \right) \left(0.22481 \frac{\text{lb}}{\text{N}} \right) \left[\frac{1 \text{ m}^2}{(3.2808)^2 \text{ ft}^2} \right]$$

$$= 2.089 \times 10^{-2} \frac{\text{lb}}{\text{ft}^2}$$

Thus, multiply N/m^2 by 2.089 E-2 to convert to lb/ft^2 .

$$(d) \quad 1 \frac{\text{m}^3}{\text{s}} = \left(1 \frac{\text{m}^3}{\text{s}} \right) \left[(3.2808)^3 \frac{\text{ft}^3}{\text{m}^3} \right] = 35.31 \frac{\text{ft}^3}{\text{s}}$$

Thus, multiply m^3/s by 3.531 E+1 to convert to ft^3/s .

1.25

1.25 Water flows from a large drainage pipe at a rate of 1200 gal/min. What is this volume rate of flow in (a) m^3/s , (b) liters/min, and (c) ft^3/s ?

$$\begin{aligned} \text{(a)} \quad \text{flowrate} &= \left(1200 \frac{\text{gal}}{\text{min}} \right) \left(6.309 \times 10^{-5} \frac{\text{m}^3}{\text{s}} \frac{\text{gal}}{\text{min}} \right) \\ &= \underline{\underline{7.57 \times 10^{-2} \frac{\text{m}^3}{\text{s}}}} \end{aligned}$$

$$\text{(b) Since } 1 \text{ liter} = 10^{-3} \text{ m}^3,$$

$$\begin{aligned} \text{flowrate} &= \left(7.57 \times 10^{-2} \frac{\text{m}^3}{\text{s}} \right) \left(\frac{10^3 \text{ liters}}{\text{m}^3} \right) \left(\frac{60 \text{ s}}{\text{min}} \right) \\ &= \underline{\underline{4540 \frac{\text{liters}}{\text{min}}}} \end{aligned}$$

$$\begin{aligned} \text{(c) flowrate} &= \left(7.57 \times 10^{-2} \frac{\text{m}^3}{\text{s}} \right) \left(3.531 \times 10 \frac{\text{ft}^3}{\text{m}^3} \right) \\ &= \underline{\underline{2.67 \frac{\text{ft}^3}{\text{s}}}} \end{aligned}$$

1.26 Dimensionless combinations of quantities (commonly called dimensionless parameters) play an important role in fluid mechanics. Make up five possible dimensionless parameters by using combinations of some of the quantities listed in Table 1.1.

Some possible examples:

$$\frac{\text{acceleration} \times \text{time}}{\text{velocity}} \doteq \frac{(LT^{-2})(T)}{(LT^{-1})} \doteq L^0 T^0$$

$$\frac{\text{frequency} \times \text{time}}{\text{frequency} \times \text{time}} \doteq (T^{-1})(T) \doteq T^0$$

$$\frac{(\text{velocity})^2}{\text{length} \times \text{acceleration}} \doteq \frac{(LT^{-1})^2}{(L)(LT^{-2})} \doteq L^0 T^0$$

$$\frac{\text{force} \times \text{time}}{\text{momentum}} \doteq \frac{(F)(T)}{(M LT^{-1})} \doteq \frac{(F)(T)}{(FT^2 L^{-1})(LT^{-1})} \doteq F^0 L^0 T^0$$

$$\frac{\text{density} \times \text{velocity} \times \text{length}}{\text{dynamic viscosity}} \doteq \frac{(ML^{-3})(LT^{-1})(L)}{ML^{-1} T^{-1}} \doteq M^0 L^0 T^0$$

1.27

1.27 An important dimensionless parameter in certain types of fluid flow problems is the *Froude number* defined as V/\sqrt{gl} , where V is a velocity, g the acceleration of gravity, and l a length. Determine the value of the Froude number for $V = 10$ ft/s, $g = 32.2$ ft/s², and $l = 2$ ft. Recalculate

the Froude number using SI units for V , g , and l . Explain the significance of the results of these calculations.

In BG units,

$$\frac{V}{\sqrt{gl}} = \frac{10 \frac{\text{ft}}{\text{s}}}{\sqrt{(32.2 \frac{\text{ft}}{\text{s}^2})(2 \text{ft})}} = \underline{\underline{1.25}}$$

In SI units:

$$V = (10 \frac{\text{ft}}{\text{s}}) (0.3048 \frac{\text{m}}{\text{ft}}) = 3.05 \frac{\text{m}}{\text{s}}$$

$$g = 9.81 \frac{\text{m}}{\text{s}^2}$$

$$l = (2 \text{ft}) (0.3048 \frac{\text{m}}{\text{ft}}) = 0.610 \text{m}$$

Thus,

$$\frac{V}{\sqrt{gl}} = \frac{3.05 \frac{\text{m}}{\text{s}}}{\sqrt{(9.81 \frac{\text{m}}{\text{s}^2})(0.610 \text{m})}} = \underline{\underline{1.25}}$$

The value of a dimensionless parameter is independent of the unit system.